CF09K6E-PFV

HFC, R-404A, 60Hz, 1- Phase, 208/230 V
Low Temperature

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	-10 / 120	-25 / 105
RG(°F)/Liq(°F)	40 / 120	40 / 105
Capacity (Btu/hr)	9800	7040
Power (Watts):	2470	1850
Current (Amps):	11.20	8.60
EER (Btu/Wh):	4.00	3.80
Mass Flow (lbs/hr):	224	140
Sound Power (dBA):	0 Avg	0 Max
Vibration (mils(peak-	0.0 Avg	0.0 Max
Record Date:	2002-11-11	

Mechanical

Number of Cylinders:	2	Displ(in^3/Rev):	4.40
Bore Size(in):	1.96	Displ(ft^3/hr):	534.59
Stroke(in):	0.73		
Overall Length (in):	10.23	Mounting Length (in):	7.50
Overall Width (in):	9.65	Mounting Width (in):	7.50
Overall Height (in):	13.81	Mounting Height (in):	14.19 *

Suction Size (in):	3/4
Discharge Size (in):	1/2
Oil Recharge (oz):	43
Initial Oil Charge (oz):	45
Net Weight (lbs):	69
Internal Free Volume (in^3):	470.0
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*:	87.0	MCC (Amps):	23.4	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	26-Apr-2000
LRA Low*:		Max Operating Current:	18.7		
RLA(=MCC/1.4;use for contactor selection):		16.7			
RLA(=MCC/1.56;use for breaker & wire size		15			

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-404A HFC	50	1	200	Low Temperature
R-507 HFC	50	1	200	
R-507 HFC	60	1	208/230	

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.