ZF15K4E-TF5

HFC, R-404A, 60Hz, 3- Phase, 200/230 V
Low Temp, Low Condensing

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	-25 / 50	-40 / 50
RG(°F)/Liq(°F)	65 / 50	65 / 50
Capacity (Btu/hr)	22500	15400
Power (Watts):	2060	1900
Current (Amps):	8.30	8.10
EER (Btu/Wh):	10.90	8.10
Mass Flow (lbs/hr):	297	202
Sound Power (dBA):	78 Avg	83 Max
Vibration (mils(peak-	2.0 Avg	3.0 Max
Record Date:	2004-03-26	

Mechanical

Number of Cylinders:	0	Displ(in^3/Rev):	5.04
Bore Size(in):	0.00	Displ(ft^3/hr):	612.50
Stroke(in):	0.00		
Overall Length (in):	11.16	Mounting Length (in):	7.50
Overall Width (in):	9.67	Mounting Width (in):	7.50
Overall Height (in):	18.50	Mounting Height (in):	19.25 *

Suction Size (in):	7/8 Stub
Discharge Size (in):	1/2 Stub
Oil Recharge (oz):	60
Initial Oil Charge (oz):	64
Net Weight (lbs):	80
Internal Free Volume (in^3):	363.0
Horse Power:	5

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*:	123	MCC (Amps):	26.5	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	15-Jun-1994
LRA Low*:		Max Operating Current:	22.0		
RLA(=MCC/1.4;use for contactor selection):		18.9			
RLA(=MCC/1.56;use for breaker & wire size		17			

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-134a HFC	50	3	200/220	High Temperature
R-134a HFC	50	3	200/220	Low Temp, Liquid Injected
R-134a HFC	50	3	200/220	Medium Temp, Liquid Injected
R-22 HCFC	50	3	200/220	Low Temp, Liquid Injected
R-22 HCFC	50	3	200/220	Medium Temp, Liquid Injected
R-404A HFC	50	3	200/220	Low Temp, Low Condensing
R-404A HFC	50	3	200/220	Low Temp, Liquid Injected
R-404A HFC	50	3	200/220	Medium Temp, Liquid Injected
R-407A HFC	50	3	200/220	
R-407A HFC	50	3	200/220	
R-407C HFC	50	3	200/220	

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-407C HFC	50	3	200/220	
R-507 HFC	50	3	200/220	Low Temp, Low Condensing
R-507 HFC	50	3	200/220	Low Temp, Liquid Injected
R-507 HFC	50	3	200/220	Medium Temp, Liquid Injected
R-134a HFC	60	3	200/230	High Temperature
R-134a HFC	60	3	200/230	Low Temp, Liquid Injected
R-134a HFC	60	3	200/230	Medium Temp, Liquid Injected
R-22 HCFC	60	3	200/230	Low Temp, Liquid Injected
R-22 HCFC	60	3	200/230	Medium Temp, Liquid Injected
R-404A HFC	60	3	200/230	Low Temp, Liquid Injected
R-404A HFC	60	3	200/230	Medium Temp, Liquid Injected
R-407A HFC	60	3	200/230	
R-407A HFC	60	3	200/230	
R-407A HFC	60	3	200/230	Low Temp, Liquid Injected
R-407C HFC	60	3	200/230	
R-407C HFC	60	3	200/230	
R-407C HFC	60	3	200/230	Low Temp, Liquid Injected
R-507 HFC	60	3	200/230	Low Temp, Low Condensing
R-507 HFC	60	3	200/230	Low Temp, Liquid Injected
R-507 HFC	60	3	200/230	Medium Temp, Liquid Injected

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.