CR60K5-PFV

HCFC, R-22, 60Hz, 1- Phase, 208/230 V
Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	58500	75000
Power (Watts):	5750	4660
Current (Amps):	25.90	20.90
EER (Btu/Wh):	10.10	16.10
Mass Flow (lbs/hr):	855	965
Sound Power (dBA):	79 Avg	84 Max
Vibration (mils(peak-	5.0 Avg	6.0 Max
Record Date:	2012-02-13	

Mechanical

Number of Cylinders:	2	Displ(in^3/Rev):	5.82
Bore Size(in):	1.96	Displ(ft^3/hr):	706.92
Stroke(in):	0.96		
Overall Length (in):	11.38	Mounting Length (in):	7.50
Overall Width (in):	9.38	Mounting Width (in):	7.50
Overall Height (in):	15.88	Mounting Height (in):	16.25 *

Suction Size (in):	7/8 Stub
Discharge Size (in):	1/2 Stub
Oil Recharge (oz):	66
Initial Oil Charge (oz):	70
Net Weight (lbs):	87
Internal Free Volume (in^3):	
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*:	135.0	MCC (Amps):	43.0	UL File No:
LRA-Half Winding:		RPM:	3500	UL File Date:
LRA Low*:		Max Operating Current:		
RLA(=MCC/1.4;use for contactor selection):		30.7		
RLA(=MCC/1.56;use for breaker & wire size		27.6		

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0006-13	189.0	227.0	330	HIGH TORQUE
Run Capacitor	014-0064-15	45.0	0.0	440	
Start Capacitor	014-0064-15	45.0	0.0	440	LOW TORQUE

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-502 CFC	50	1	200	
R-502 CFC	60	1	208/230	
R-22 HCFC	50	1	200	Air Conditioning

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.