ZP24K5E-TF5

HFC, R-410A, 60 Hz, 3 - Phase, 200/230 V , Also Available with Variable Frequency Drives

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance

Evaporator Temp. (°F)	45.00	50
Condensing Temp. (°F)	130.00	100
Return Gas Temp. (°F)	65.00	70
Liquid Temp. (°F)	115.00	85
Capacity (BTU/hr)	24000	32800
Power (W):	2420	1570
Current (Amps):	7.3	5.3
EER(BTU/Wh):	9.9	20.9
Mass Flow (lbs/hr):	353	403
Sound Data @ 45 / 130		
Sound Power (dBA):	69 Avg	74 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2017-03-01	

Mechanical

Displacement (in^3/Rev):	1.39
Displacement (ft^3/Hr):	
Overall Length (in):	9.69
Overall Width (in):	9.69
Overall Height (in):	15.28
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	16.03
Suction Size (in),Type:	3 / 4 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	25
Oil Recharge (oz):	21
Oil Type:	3MA
Net Weight (lbs):	46.8
Internal Free Volume (in^3):	129.6

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	58.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	13
Max Operating Current (Amps):	9.50
RLA, MCC/1.4(use for contactor selection)(Amps):	9.3
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.3
RPM:	3500
Box IP :	56
UL File No:	SA2337-20031216
UL File Date:	2003-12-16

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description

No data available in table

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	200/220	3	50	Air Conditioning