ZP42K5E-TF5

HFC, R-410A, 60Hz, 3- Phase, 200/230 V
Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	50 / 100
RG(°F)/Liq(°F)	65 / 115	70 / 85
Capacity (Btu/hr)	41900	57600
Power (Watts):	4060	2640
Current (Amps):	11.30	7.95
EER (Btu/Wh):	10.30	21.80
Mass Flow (lbs/hr):	618	708
Sound Power (dBA):	71 Avg	76 Max
Vibration (mils(peak-	2.0 Avg	3.0 Max
Record Date:	2008-10-02	

Mechanical

Number of Cylinders:	0	Displ(in^3/Rev):	2.43
Bore Size(in):	0.00	Displ(ft^3/hr):	295.31
Stroke(in):	0.00		
Overall Length (in):	9.56	Mounting Length (in):	7.50
Overall Width (in):	9.56	Mounting Width (in):	7.50
Overall Height (in):	16.94	Mounting Height (in):	17.17 *

Suction Size (in):	7/8 Stub
Discharge Size (in):	1/2 Stub
Oil Recharge (oz):	38
Initial Oil Charge (oz):	42
Net Weight (lbs):	67
Internal Free Volume (in^3):	209.5
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*:	83.1	MCC (Amps):	21.4	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	17-Dec-2003
LRA Low*:		Max Operating Current:	15.0		
RLA(=MCC/1.4;use for contactor selection):		15.3			
RLA(=MCC/1.56;use for breaker & wire size		13.7			

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-410A HFC	50	3	200/220	Air Conditioning

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.