ZP154KCE-TWD

HFC, R-410A, 60Hz, 3- Phase, 460 V
Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	35 / 120
RG(°F)/Liq(°F)	65.0 / 115.0	55.0 / 105.0
Capacity (Btu/hr)	155000	138000
Power (Watts):	14000	12400
Current (Amps):	21.00	19.00
EER (Btu/Wh):	11.10	11.10
Mass Flow (lbs/hr):	2290	1930
Sound Power (dBA):	80 Avg	85 Max
Vibration (mils(peak-peak)):	3.0 Avg	4.5 Max
Record Date:	2007-10-31	

Mechanical

Number of Cylinders:	0	Displ(in^3/Rev):	8.72
Bore Size(in):	0.00	Displ(ft^3/hr):	1059.85
Stroke(in):	0.00		
Overall Length (in):	12.83	Mounting Length (in):	7.50
Overall Width (in):	11.61	Mounting Width (in):	7.50
Overall Height (in):	21.72	Mounting Height (in):	23.03 *

Suction Size (in):	1 3/8 Stub
Discharge Size (in):	7/8 Stub
Oil Recharge (oz):	106
Initial Oil Charge (oz):	110
Net Weight (lbs):	143
Internal Free Volume (in^3):	856.0
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*:	150.0	MCC (Amps):	36.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	27-Sep-1996
LRA Low*:		Max Operating Current:	27.0		

RLA(=MCC/1.4;use for contactor selection): 25.7

RLA(=MCC/1.56;use for breaker & wire size selection): 23.1

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-410A HFC	50	3	380/420	Air Conditioning

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.