ZP385KCE-TED

HFC, R-410A, 60 Hz, 3 -Phase, 460 V
Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	35
Condensing Temp. (°F)	130	120
Return Gas Temp. (°F)	65	55
Liquid Temp. (°F)	115	105
Capacity (Btu/hr)	385000	343000
Power (W):	34700	30600
Current (Amps):	49.90	44.60
EER (Btu/Wh):	11.10	11.20
Mass Flow (lbs/hr):	5650	4790
Sound Data @		
Sound Power (dBA):	89 Avg	94 Max
Vibration mils(peak-peak):	3.5 Avg	5.0 Max
Record Date:	2017-07-06	

Mechanical

Displacment(in^3/Rev):	21.32
Displacment(ft^3/hr):	2590.98
Overall Length (in):	17.60
Overall Width (in):	16.80
Overall Height (in):	28.50
Mounting Length (in):	10.50
Mounting Width (in):	10.50
Mounting Height (in):	28.90 *
Suction Size (in),Type:	1 5/8 Stub
Discharge Size (in),Type:	1 3/8 Stub
Initial Oil Charge (oz):	213
Oil Recharge (oz):	203
Net Weight (lbs):	390.0
Internal Free Volume (in^3):	1931.0
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):	310.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	85.0
Max Operating Current(Amp):	65.4
RLA, MCC/1.4;use for contactor selection (Amp):	60.7
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	54.5
RPM:	3500
Box IP	56
UL File No:	SA-2337
UL File Date:	2000-11-28

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-410A HFC	380/420	3	50	Air Conditioning

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.